



GAFLAS®

STRATAVENT® NAILABLE VENTING BASE SHEET

Formerly GAFLAS® Stratavent® Eliminator™
Nailable Venting Base Sheet



Description

GAFLAS® Stratavent® Nailable Venting Base Sheet is a premium-grade roofing felt constructed around a strong glass fiber mat and high-quality asphalt. The bottom of the sheet is granule-surfaced to provide positive venting of any trapped gases under the roof membrane.

- GAFLAS® Stratavent® Nailable Venting Base Sheet is available for nailable and non-nailable substrates.
- GAFLAS® Stratavent® Nailable Venting Base Sheet is mechanically attached to wood, structural wood fiber, poured gypsum, and lightweight insulating concrete decks.

Uses

GAFLAS® Stratavent® Nailable Venting Base Sheet is a venting base sheet designed to be used in various GAFLAS® built-up and RUBEROID® modified bitumen roofing systems. It can be used over both nailable and non-nailable substrates, including certain existing old roof surfaces and isocyanurate foams.

Advantages

- Provides for venting of pressurized gases beneath the roofing membrane.
- Fire resistant—for use in UL Class A rated assemblies.
- In re-cover applications, provides an effective means for separating the new roofing membrane from the existing roof system.
- Wind uplift-resistant; FM Approved up to Class 1-345 (see FM Approval Guide for details).
- Meets requirements for application in all climate zones.
- System guarantees are available for up to 20 years.*

Applicable Standards

Meets ASTM D4897, Type II
FM Approved
ICC ESR-274
Miami-Dade County Product Control Approved
State of Florida Approved
Texas Department of Insurance
UL/ULC Listed

Product Specifications (nominal)

Roll Size	1.26 squares (133.4 gross sq. ft.) (12.4 m²)
Roll Length	40.6' (9.9 m)
Roll Width	39.375" (1.0 m)
Approx. Roll Weight	79 lb (35.8 kg)

* See applicable guarantee for complete coverage and restrictions.